Report of Humbodt University Berlin (Team Name: Humboldt Heroes)

Prof. H. D. Burkhard, Dr. M. Ritzschke, Dr. F. Winkler,
Dr. M. Werner, A.Georgi, U. Dueffert, H. Myritz

14th September 1999

Contents

1 Overview

The team members include students as well as members of the teaching stuff from the Institute of Informatics at the Humboldt University.
They represent the groups of Artificial Intelligence, Responsive Computing, and Signal Processing, respectively.
It was the aim of the project to combine the skills of these disciplines to program football playing legged robots.

An underlying idea was to use the experiences from the simulation league for the general structure of the robot software. We still think that this concept is realistic. But the restricted time forced us to use a very simple reactive approach for the RoboCup 1999.

Our general research interests can be described as follows:

We are using methods from Distributed AI for knowledge processing and control, based on mental models of deliberation. We are interested in the development of skills on higher level decision protocols using methods from Machine Learning, especially from Case Based Reasoning.
We are specifically interested in developing normal consensus protocols, collision avoidance protocols and would like to develop new models of faults, e.g., the opposing soccer team would be considered as a new type of a fault.

We are interested in novel algorithms for image processing and their implementation in embedded systems. We would like to apply parallel computing structures for image processing using the pixel-bit parallelism principles of distributed arithmetic. Scalable resolution allows simultaneous suppression of noise, sharpening of discontinuities and labelling of important data.

2 Strategy

We have experience in the design of agent architectures for the simulation league, where we have used belief-desire-intention approaches. There we have developed a couple of basic skills (e.g. for kicking, dribbling, ball interception). The choice of desires and intentions is based on utility calculations, which lead to individual plans on the base of the available skills. Cooperation is performed using the known behaviors of team mates.
We already have some experience with robots where robots need to cooperate to execute a specific task. Our approach is based on CORE (COnsensus for

REsponsiveness) middleware which was developed by our group for a cluster of workstations. In this project we will add an extra level of difficulty by modeling hostile faults. We also plan to use sophisticated search techniques such as Tabu Search and Simulated Annealing to develop a strategy and decide on particular moves.

Furthermore, we have some experience in hardware/software co-design and implementing low level signal processing procedures for recognition tasks both in hardware and in software.

We got some experience in implementation of effective control methods from experiments with the minirobot system KHEPERA. So we could make comparisons between decision- rules-controller and fuzzy-logic-controller.

3 Algorithm

We have distinguished four main parts which we call Cortex, Brain, Body, and Communication. Messages are passed between these modules according to the underlying control structure.

3.1 Walking, and Posture control

The general idea is to transmit the plans computed by the Brain to the Body and performed it by the available skills. The Body controls the movement of the legs in order to turn, move, kick etc. Additionally, there exists a direct information flow between Cortex and Body for immediate actions, e.g., for keeping track of the ball. This imposes some rudimentary layered architecture.
Realization: We did not develop our own skills. This was a real drawback since the usage of the available skills (LE2 module) caused several problems. The main disadvantage was a missed possibility to interrupt a movement in process. Another disadvantage was a lack of movements' precision.
We tried to overcome these disadvantages by several means:

- To interrupt a movement, we insert an interception function between LE2 module and the robot module. Its task was to intercept outgoing commands and to report success to the LE2 module.
- To improve the real-time behavior, we used a priority queue to transmit commands to the body. Sent but not yet executed command that became superfluous are throw away.



Figure 1: CDT-contents in the HLS space

- Critical parts of a movement are executed in the step-wise mode. That shall increase the movement's accuracy.

However, the creation of a real-time walking and posture control is a mayor objective to become an appropriate competitor in the next competition.

3.2 Vision (Color recognition and how to make color table)

The Cortex uses the Color Detection Engine to identify the objects in the image by common procedures of image-processing to find the object parameters, e.g. position, width, center-point. The control of head motions is subject of the Cortex.

3.2.1 Generating of CDTs with a colour simulation tool

It is well known, there are some possibilities to describe the colour in a picture. Common colour spaces are for instance RGB, YUV (the PAL/European standard for colour television broadcasting) and HLS(Fig.1), where H is for the Hue (the H value is a degree value through colour families), L for Lightness (1 = white, 0 = black) and S fore Saturation (that is the degree of strength of a colour - greater is S, the purest is the colour).

The robot-eye use the YUV space and so we can analyze the YUV-values in a robot-image. But we want to create CDTs for a wide range of lightness/darkness and of saturation, because the robot sees different colours in the pictures if he looks from different viewpoint to the same objects. On the other side we found in our testing-period, that every robot had from the same viewpoint under the same light conditions little different YUV-values.

Therefore we realize a way to develop our CDT's with four steps:

Step 1:

Shooting session to get some images from all relevant objects (ball, goals, player-dress, landmarks), we use different viewpoints and - if enough time, all our robots.

Step 2:(Fig.2)
Analyzing of the YUV values and transformation via RGB in the HLS space. Our tool allows us to use the mouse for moving a reticule over the object. With the help of the statistical componente we get for H,L,S the mean value and the standard deviation.

Step 3:
Now we use a second tool (Fig.3) to simulate possible combinations of HLS around the mean values of H,L,S - with the help of random numbers of the constant distribution like radio noise. Every generated HLS-point (we use ¿ 1000 points) will be transformated in the YUV space and the resulting borderlines of YU and YV plane built our CDTs, which we can save in a file(Fig.4).

Step 4:
Checking: We check the quality of our CDTs with a further program using originally robot-images.
This tool allows - if it is necessary - manually corrections of the CDTs.